

Model(s) **UltraTec**  
 Model Year **2006**  
 Limbs **XT2000**  
 Cable Guard Bar **8 1/2**  
 Limb Bolt Length **2 1/2**  
 Pocket **25 & 26**

Date **12/8/2005**

Revision

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Module Position	Base Cam	String	control cable	buss cable
	65/75	6 13/16	36 3/4	25	E	C&1/2 #1	49.5	40.5	38.25
cam	65/75	6 3/4	37 1/8	26	E	C&1/2 #2	51	41	38.75
& 1/2	65/75	6 13/16	37 1/8	27	E	C&1/2 #3	52	41.5	38.75
adjustable	65/75	6 13/16	37 1/8	28	E	C&1/2 #4	53.5	42	39.25
	65/75	6 15/16	37 1/4	29	E	C&1/2 #5	55	42	39.25
	65/75	7	37 1/2	30	E	C&1/2 #6	56.5	42.75	39.75
	65/75	7	37 3/4	31	E	C&1/2 #7	58	43.5	40

Cam / Wheel	% Letoff	Brace Height	Axle to Axle	Draw Length	Base Cam	String	control Cable	Buss Cable
	65%	6 1/2	36 5/8	24	1	54.5	41.25	38.5
	65%	6 1/2	36 5/8	24 1/2	1 1/2	54.5	41.25	38.5
	65%	6 1/2	36 9/16	25	2	54.5	41.25	38.5
	65%	6 1/2	36 9/16	25 1/2	2 1/2	54.5	41.25	38.5
	65%	6 5/8	36 1/4	26	3	56	41.5	38.5
	65%	6 5/8	36 1/4	26 1/2	3 1/2	56	41.5	38.5
cam	65%	6 5/8	36 1/4	27	4	56	41.5	38.5
& 1/2	65%	6 11/16	36 3/8	27 1/2	4 1/2	57.75	41.5	38.25
spiral	65%	6 11/16	36 3/8	28	5	57.75	41.5	38.25
	65%	6 11/16	36 3/8	28 1/2	5 1/2	57.75	41.5	38.25
	65%	6 11/16	36 5/8	29	6	59.5	41.5	38.5
	65%	6 11/16	36 5/8	29 1/2	6 1/2	59.5	41.5	38.5
	65%	6 11/16	36 5/8	30	7	59.5	41.5	38.5
	65%	6 3/4	36 5/8	30 1/2	7 1/2	61	42.25	38.25
	65%	6 3/4	36 5/8	31	8	61	42.25	38.25