

## 2013 PRIME DEFY BOW SPEC SHEET

**A/A:** 31.30" +/- 0.10"

**B.H.:** 7.2" +/- 0.10"

**D.L.:** +3/8"

**String:** 24.060"

**Cable:** 37.530"

**Yoke:** 33.790"

CAMS:	DRAW LENGTH <sup>1</sup> :	IBO RATING <sup>2</sup> :
PCX#1	30"	326-321
PCX#2	29.5"	321-316
PCX#3	29"	316-311
PCX#4	28.5"	311-306
PCX#5	28"	306-301
PCX#6	27.5"	301-291
PCX#7	27"	291-286
PCX#8	26.5"	286-281
PCX#9	26"	281-276

Limb Deflections:	Draw Weights:
132	52-50
111	62-60
95	72-70

**Cam System:** PARALLEL Cam System-(PCX)  
**Let-Off:** 75%  
**Spacers:** .080/.085" on both sides<sup>3</sup>  
**Suppressor Rod:** P/N: W-000129 (Prime 2-Shot S.S. Assembly-Long)  
**Ti-Glide:** P/N: W-000131 (Prime 7" Cable Glide Assembly-Grey)  
**Bearings:** P/N: 12216  
**Pivots:** P/N: R-000027(Blue)  
**Timing:** Hole half under limb +/-0.5 Hole

BachofnerBogenSport.ch

Notes:

- 1.) Minus nothing, plus 1/4"
- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005" to be within .005" from side to side.



QF-697 Defy Bow Specification Sheet  
 Rev. 1

Approved By: Scott Prater Date: 12/18/13

