

2014 PRIME ALLOY SPEC SHEET

A/A: 33.30" +/- 0.10"

B.H.: 6.7" +/- 0.10"

D.L.: +3/8"

String: 26"

Cable: 39.4"

Yoke: 33.75"

CAMS:	DRAW LENGTH ¹ :	IBO RATING ² :
PCX#1	30"	331-326
PCX#2	29.5"	326-321
PCX#3	29"	321-316
PCX#4	28.5"	316-311
PCX#5	28"	311-301
PCX#6	27.5"	301-296
PCX#7	27"	296-291
PCX#8	26.5"	291-286
PCX#9	26"	286-281

Limb Deflections:	Draw Weights:
132	52-50
111	62-60
95	72-70

Cam System: PARALLEL Cam System-(PCX)
Let-Off: 75%
Spacers: .080" on both sides³
Suppressor Rod: P/N: R-000130 (rod) & R-000005 (bumper)
Bearings: P/N: 12216
Pivots: P/N: R-000027(Blue)
Timing: Hole half under limb +/-0.5 Hole

BachofnerBogenSport.ch

Notes:

- 1.) Minus nothing, plus 1/4"
- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005" to be within .005" from side to side.

