

2013 PRIME IMPACT SPEC SHEET

A/A: 35.30" +/- 0.10"

B.H.: 6.13" +/- 0.10"

D.L.: +3/8"

String: 28.152"

Cable: 41.437"

Yoke: 33.790"

CAMS:	DRAW LENGTH ¹ :	IBO RATING ² :
PCX#1	30"	336-331
PCX#2	29.5"	331-326
PCX#3	29"	326-321
PCX#4	28.5"	321-316
PCX#5	28"	316-311
PCX#6	27.5"	311-301
PCX#7	27"	301-296
PCX#8	26.5"	296-291
PCX#9	26"	291-286

Limb Deflections:	Draw Weights:
132	52-50
111	62-60
95	72-70

Cam System: PARALLEL Cam System-(PCX)
Let-Off: 75%
Spacers: .080 / .085" on both sides³
Suppressor Rod: P/N: R-000130 (Prime 2-Shot S.S. Assembly-Black)
Ti-Glide: P/N: W-000144 (Prime 6" Cable Glide Assembly-Black Target/Grey -Camo)
Bearings: P/N: 12216
Pivots: P/N: R-000027(Blue)
Timing: Hole half under limb +/-0.5 Hole

BachofnerBogenSport.ch

Notes:

- 1.) Minus nothing, plus ¼"
- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005" to be within .005" from side to side.



QF-696 Impact Bow Specification Sheet
 Rev. 1

Approved By: Scott Prater Date: 12/18/13

